EcoMarble® Applications & Suitability Guide

Premium Residential, Hospitality, Office, Retail & Commercial Interiors

EcoMarble® | A Nusfun Brand

1. Application Matrix

Application	Positioning	Key Conditions	Typical Project Types
Interior dry walls / feature walls	Generally suitable	Sound, flat, clean substrate; use an adhesive system compatible with both substrate and composite backing.	Residential, hotels, resorts, offices, retail, lobbies
Bathroom / wet-area walls	Conditional	Compliant waterproofing; complete adhesive, sealing, penetration and junction detailing; qualified installation.	Residential, hotels, resorts
Overlay over existing tiles	Conditional	Confirm existing tiles are sound, stable and flat; address contamination, drummy tiles and cracks; confirm primer and adhesive compatibility.	Residential renovation, hotel refurbishment, selected commercial fit-outs
Kitchen splashbacks	Conditional	Review heat-source clearance, joints, sealants, cleaning regime and substrate conditions.	Residential, serviced apartments, selected hotel/food-service spaces
Joinery / furniture / selected decorative surfaces	Project-specific	Review panel movement, edge details, fabrication method, fixing method and substrate stability.	Residential, hospitality, office, retail
Floors	Separate assessment	Review slip resistance, loads, impact, substrate, adhesive system, joints and traffic intensity.	Project-specific assessment only
Exterior façades	Separate assessment	Engineering design required; review weather exposure, wind loads, fixing, movement and safety.	Project-specific assessment only
Overhead / ceilings	Separate assessment	Engineering design required; review mechanical restraint/fixing, substrate and safety.	Project-specific assessment only

EcoMarble full-size samples and finish display

2. Recommended Project Suitability Review

- Confirm project location, building type, application area and estimated quantity.
- Confirm substrate type, flatness, stability and moisture/contamination conditions.
- For wet areas, confirm waterproofing, penetrations, joints and sealing details.

- Provide preferred stone, finish, drawings, photos or relevant details.
- Confirm proposed adhesive, fixing and installation system.

3. Natural Stone Note

Natural stone varies in colour, veining, mineral features and tone. Website, catalogue and photographic images are selection references only; final project approval should be based on physical samples, batch confirmation and site conditions.